
Two hole 45°




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Pink	42
Panduit	CT-720 CT-920	Pink	P42
Burndy	MY29 Y644M	Pink	12
Celestra	A45	Pink	42

	Wire Size		Dimension (in.)						
Cat. Nos	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	G	R	ID	Std. Pkg.
DB101434F	#1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.55	0.75	0.75	0.98	0.40	100
DB103801F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.93	0.75	1.00	0.98	0.40	100
LB101401F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.88	0.75	1.00	1.33	0.40	100
LB101401FP	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.88	0.75	1.00	1.33	0.40	100
LB101458F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.19	0.75	0.63	1.33	0.40	100
LB101434F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.38	0.75	0.75	1.33	0.40	100
LB105678F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.63	0.75	0.88	1.33	0.40	100
LB103801F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.98	0.75	1.00	1.33	0.40	100
LB103801FP	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.93	0.75	1.00	1.33	0.40	100
LB101243F	1/0AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	3.00	0.75	1.75	1.33	0.40	100
DB101458F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.33	0.76	0.63	1.22	0.39	100
DB101434F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.45	0.76	0.75	1.22	0.39	100
DB105678F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.64	0.76	0.88	1.22	0.39	100
DB103801F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.83	0.76	1.00	1.22	0.39	100
DB101243F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	3.01	0.80	1.75	1.22	0.39	100
DB105678F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.57	0.75	0.88	1.16	0.39	100
DB101243F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	2.83	0.83	1.75	1.16	0.39	100
DB101458F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.26	0.75	0.62	1.16	0.39	100
DB101401F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.64	0.75	1.00	1.16	0.39	100
DB101434F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.39	0.75	0.75	1.16	0.39	100
DB103801F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.83	0.75	1.00	1.16	0.39	100
DB101458F-251	1/0 AWG	275/24 1/0 Weld	1/4	1.41	0.85	0.63	1.00	0.45	100
DB101434F-251	1/0 AWG	275/24 1/0 Weld	1/4	1.53	0.85	0.75	1.00	0.45	100
DB105634F-251	1/0 AWG	275/24 1/0 Weld	5/16	1.53	0.85	0.75	1.00	0.45	100
DB105601F-251	1/0 AWG	275/24 1/0 Weld	5/16	1.78	0.85	1.00	1.00	0.45	100
DB103801F-251	1/0 AWG	275/24 1/0 Weld	3/8	1.84	0.85	1.00	1.00	0.45	100
DB101201F-251	1/0 AWG	275/24 1/0 Weld	1/2	2.09	0.85	1.00	1.00	0.45	100
DB101243F-251	1/0 AWG	275/24 1/0 Weld	1/2	3.01	0.85	1.75	1.00	0.45	100
DB101458F-261	1/0 AWG	275/24 1/0 Weld	1/4	1.26	0.83	0.62	0.97	0.44	100
DB101434F-261	1/0 AWG	275/24 1/0 Weld	1/4	1.39	0.83	0.75	0.97	0.44	100
DB105634F-261	1/0 AWG	275/24 1/0 Weld	5/16	1.45	0.83	0.75	0.97	0.44	100
DB105601F-261	1/0 AWG	275/24 1/0 Weld	5/16	1.70	0.83	1.00	0.97	0.44	100
DB103801F-261	1/0 AWG	275/24 1/0 Weld	3/8	1.83	0.83	1.00	0.97	0.44	100
DB101201F-261	1/0 AWG	275/24 1/0 Weld	?1/2	2.08	0.83	1.00	0.97	0.44	100
DB101243F-261	1/0 AWG	275/24 1/0 Weld	?1/2	2.83	0.83	1.75	0.97	0.44	100
WP101434F-139	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.79	0.74	0.75	0.91	0.40	100

© 2002 HUYA Corporation. Specifications are subject to change without notice.**www.huyaco.com**

Two hole 45°




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Pink	42
Panduit	CT-720 CT-920	Pink	P42
Burndy	MY29 Y644M	Pink	12
Celestra	A45	Pink	42

	Wire Size		Dimension (in.)						
Cat. Nos	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	G	R	ID	Std. Pkg.
LB101458F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.33	0.76	0.63	1.72	0.39	100
LB101434F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.45	0.76	0.75	1.72	0.39	100
LB105678F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.64	0.76	0.88	1.72	0.39	100
LB105601F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.76	0.76	1.00	1.72	0.39	100
LB103801F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.83	0.76	1.00	1.72	0.39	100
LB101201F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	2.10	0.80	1.00	1.72	0.39	100
LB101243F-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	3.01	0.80	1.75	1.72	0.39	100
LB101458FP-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.33	0.76	0.63	1.72	0.39	100
LB101434FP-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.45	0.76	0.75	1.72	0.39	100
LB103801FP-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.83	0.76	1.00	1.72	0.39	100
LB103843FP-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	2.58	0.76	1.75	1.72	0.39	100
LB101201FP-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	2.10	0.80	1.00	1.72	0.39	100
LB101243FP-250	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	3.01	0.80	1.75	1.72	0.39	100
LB101243F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/2	2.83	0.81	1.75	1.66	0.39	100
LB101458F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.26	0.75	0.62	1.66	0.39	100
LB101434F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.39	0.75	0.75	1.66	0.39	100
LB103801F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.83	0.75	1.00	1.66	0.39	100
LB105601F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.70	0.75	1.00	1.66	0.39	100
LB103843F-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	2.58	0.75	1.75	1.66	0.39	100
LB101243FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	?1/2	2.83	0.83	1.75	1.66	0.39	100
LB101458FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.26	0.75	0.62	1.66	0.39	100
LB101434FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.39	0.75	0.75	1.66	0.39	100
LB101401FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	1/4	1.64	0.75	1.00	1.66	0.39	100
LB105678FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.57	0.75	0.88	1.66	0.39	100
LB105601FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	5/16	1.70	0.75	1.00	1.66	0.39	100
LB103801FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	1.83	0.75	1.00	1.66	0.39	100
LB103843FP-260	1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/.0 254	3/8	2.58	0.75	1.75	1.66	0.39	100
LB101458FP-251	1/0 AWG	275/24 1/0 Weld	1/4	1.41	0.85	0.63	1.78	0.45	100
LB101434FP-251	1/0 AWG	275/24 1/0 Weld	1/4	1.53	0.85	0.75	1.78	0.45	100
LB103801FP-251	1/0 AWG	275/24 1/0 Weld	3/8	1.84	0.85	1.00	1.78	0.45	100
LB101243FP-251	1/0 AWG	275/24 1/0 Weld	1/2	3.01	0.85	1.75	1.78	0.45	100
LB101458FP-261	1/0 AWG	275/24 1/0 Weld	1/4	1.27	0.83	0.63	1.66	0.44	100
LB101434FP-261	1/0 AWG	275/24 1/0 Weld	1/4	1.39	0.83	0.75	1.66	0.44	100

© 2002 HUYA Corporation. Specifications are subject to change without notice.**www.huyaco.com**

Two hole 45°



Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Pink	42
Panduit	CT-720 CT-920	Pink	P42
Burndy	MY29 Y644M	Pink	12
Celestra	A45	Pink	42

	Wire Size		Dimension (in.)						
Cat. Nos	Code	Flex Class G,H,I,K,M	Bolt Size	B	C	G	R	ID	Std. Pkg.
LB103801FP-261	1/0 AWG	275/24 1/0 Weld	3/8	1.83	0.83	1.00	1.66	0.44	100
LB101243FP-261	1/0 AWG	275/24 1/0 Weld	1/2	2.83	0.83	1.75	1.66	0.44	100

© 2002 HUYA Corporation. Specifications are subject to change without notice.**www.huyaco.com**