


Application for Cable Size					Dimension(mm)									Std. Pkg.
Cat. Nos	Stud(Metric)	mm²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D		
DR2202	2	0.5--1.5	22-16	6.00	5	14	0.75	11.00	6	1.7	2.2	3.4	100	
DR2225	2.5	0.5--1.5	22-16	6.00	5	14	0.75	11.00	6	1.7	2.7	3.4	100	
DR2203	3	0.5--1.5	22-16	6.00	5	14	0.75	11.00	6	1.7	3.2	3.4	100	
DR2235	3.5	0.5--1.5	22-16	6.00	5	14	0.75	11.00	6	1.7	3.7	3.4	100	
DR2204S	4	0.5--1.5	22-16	6.00	5	15	0.75	11.50	7	1.7	4.3	3.4	100	
DR2204	4	0.5--1.5	22-16	6.00	5	16	0.75	12.00	8	1.7	4.3	3.4	100	
DR2205S	5	0.5--1.5	22-16	6.00	5	16.5	0.75	12.50	8	1.7	5.3	3.4	100	
DR2205	5	0.5--1.5	22-16	6.00	5	18	0.75	13.00	10	1.7	5.3	3.4	100	
DR2206	6	0.5--1.5	22-16	6.00	5	18	0.75	13.00	10	1.7	6.5	3.4	100	
DR2206L	6	0.5--1.5	22-16	6.00	5	20.5	0.75	15.00	11	1.7	6.5	3.4	100	
DR2208	8	0.5--1.5	22-16	6.00	5	24	0.75	17.00	14	1.7	8.4	3.4	100	
DR2210	10	0.5--1.5	22-16	6.00	5	24	0.75	17.00	14	1.7	10.5	3.4	100	
DR2210L	10	0.5--1.5	22-16	6.00	5	27.5	0.75	19.00	18	1.7	10.5	3.4	100	
DR2212	12	0.5--1.5	22-16	6.00	5	29	0.75	20.00	18	1.7	13	3.4	100	
DR1603	3	1.5-2.5	16-14	6.00	5	14	0.8	11.00	6	2.3	3.2	4	100	
DR1635	3.5	1.5-2.5	16-14	6.00	5	14	0.8	11.00	6	2.3	3.7	4	100	
DR1604S	4	1.5-2.5	16-14	6.00	5	15	0.8	11.60	6.8	2.3	4.3	4	100	
DR1604	4	1.5-2.5	16-14	6.00	5	16	0.8	12.00	8	2.3	4.3	4	100	
DR1605S	5	1.5-2.5	16-14	6.00	5	17.5	0.8	13.50	8	2.3	5.3	4	100	
DR1605	5	1.5-2.5	16-14	6.00	5	19	0.8	14.00	10	2.3	5.3	4	100	
DR1606	6	1.5-2.5	16-14	6.00	5	21.5	0.8	16.00	11	2.3	6.5	4	100	
DR1608	8	1.5-2.5	16-14	6.00	5	24	0.8	17.00	14	2.3	8.4	4	100	
DR1610	10	1.5-2.5	16-14	6.00	5	24.5	0.8	17.00	15	2.3	10.5	4	100	
DR1610L	10	1.5-2.5	16-14	6.00	5	27.5	0.8	18.50	18	2.3	10.5	4	100	
DR1612	12	1.5-2.5	16-14	6.00	5	29	0.8	20.00	18	2.3	13	4	100	
DR1204S	4	4-6	12-10	7.00	6	18	1	14.00	8	3.4	4.3	5.5	100	
DR1205S	5	4-6	12-10	7.00	6	20	1	15.00	10	3.4	5.3	5.5	100	
DR1206	6	4-6	12-10	7.00	6	21.5	1	16.00	11	3.4	6.5	5.5	100	
DR1208	8	4-6	12-10	7.00	6	26	1	19.00	14	3.4	8.4	5.5	100	
DR1210	10	4-6	12-10	7.00	6	30	1	21.00	18	3.4	10.5	5.5	100	
DR1212	12	4-6	12-10	7.00	6	30	1	—	—	3.4	13	5.5	100	
DR0805	5	10	8	9.00	8	21	1.1	16.00	10	4.5	5.3	8	100	
DR0806	6	10	8	9.00	8	22.5	1.1	17.00	11	4.5	6.5	8	100	
DR0808	8	10	8	9.00	8	27	1.1	20.00	14	4.5	8.4	8	100	
DR0810	10	10	8	9.00	8	30	1.1	21.00	18	4.5	10.5	8	100	
DR0812	12	10	8	9.00	8	34	1.1	23.00	22	4.5	13	8	100	
DR0605	5	16	6	11.00	10	25.5	1.2	20.00	11	5.8	5.3	10.5	100	
DR0606	6	16	6	11.00	10	25.5	1.2	20.00	11	5.8	6.5	10.5	100	
DR0608	8	16	6	11.00	10	29	1.2	22.00	14	5.8	8.4	10.5	100	
DR0610	10	16	6	11.00	10	33	1.2	24.00	18	5.8	10.5	10.5	100	
DR0612	12	16	6	11.00	10	37	1.2	26.00	22	5.8	13	10.5	100	
DR0405	5	25	4	12.00	11	31	1.5	25.00	12	7.5	5.3	12	100	
DR0406	6	25	4	12.00	11	31	1.5	25.00	12	7.5	6.5	12	100	
DR0408	8	25	4	12.00	11	33	1.5	25.00	16	7.5	8.4	12	100	
DR0410	10	25	4	12.00	11	35	1.5	26.00	18	7.5	10.5	12	100	
DR0412	12	25	4	12.00	11	42	1.5	31.00	22	7.5	13	12	100	
DR0416	16	25	4	12.00	11	49	1.5	35.00	28	7.5	17	12	100	
DR0206	6	35	2	13.00	12	33.5	1.6	26.00	15	9	6.5	15	100	
DR0208	8	35	2	13.00	12	34	1.6	26.00	16	9	8.4	15	100	
DR0210	10	35	2	13.00	12	36	1.6	27.00	18	9	10.5	15	100	



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
DR0212	12	35	2	13.00	12	42	1.6	31.00	22	9	13	15	100
DR0216	16	35	2	13.00	12	50	1.6	36.00	28	9	17	15	100
DR1006	6	50	1/0	17.50	16	43	1.8	34.00	18	11	6.5	17	100
DR1008	8	50	1/0	17.50	16	43	1.8	34.00	18	11	8.4	17	100
DR1010	10	50	1/0	17.50	16	43	1.8	34.00	18	11	10.5	17	100
DR1012	12	50	1/0	17.50	16	47	1.8	36.00	22	11	13	17	100
DR1016	16	50	1/0	17.50	16	54	1.8	40.00	28	11	17	17	100
DR2006	6	70	2/0	19.50	18	49	2	38.00	22	13	6.5	21	100
DR2008	8	70	2/0	19.50	18	49	2	38.00	22	13	8.4	21	100
DR2010	10	70	2/0	19.50	18	49	2	38.00	22	13	10.5	21	100
DR2012	12	70	2/0	19.50	18	49	2	38.00	22	13	13	21	100
DR3008	8	95	3/0	21.50	20	54	2.5	42.00	24	15	8.4	23	100
DR3010	10	95	3/0	21.50	20	54	2.5	42.00	24	15	10.5	23	100
DR3012	12	95	3/0	21.50	20	54	2.5	42.00	24	15	13	23	100
DR3006	16	95	3/0	21.50	20	58	2.5	44.00	28	15	17	23	100
DR4008	8	120	4/0	23.50	22	56	3	44.00	24	16.5	8.4	24	100
DR4010	10	120	4/0	23.50	22	56	3	44.00	24	16.5	10.5	24	100
DR4012	12	120	4/0	23.50	22	56	3	44.00	24	16.5	13	24	100
DR4016	16	120	4/0	23.50	22	62	3	48.00	28	16.5	17	24	100
DR2510	10	150	250/300	26.00	24	65	3.2	50.00	30	19	10.5	28	100
DR2512	12	150	250/300	26.00	24	65	3.2	50.00	30	19	13	28	100
DR2516	16	150	250/300	26.00	24	65	3.2	50.00	30	19	17	28	100
DR3510	10	185	350/500	30.00	28	68	3.5	50.00	36	21	10.5	33	100
DR3512	12	185	350/500	30.00	28	68	3.5	50.00	36	21	13	33	100
DR3516	16	185	350/500	30.00	28	68	3.5	50.00	36	21	17	33	100
DR4110	10	240	400/450	34.00	32	75	4	56.00	38	23.5	10.5	36	100
DR4112	12	240	400/450	34.00	32	75	4	56.00	38	23.5	13	36	100
DR4116	16	240	400/450	34.00	32	75	4	56.00	38	23.5	17	36	100