



Application for Cable Size				Dimension(mm)							Std. Pkg.
Cat. Nos	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	D	
DP2209BS	22-16	0.5--1.5	6.00	5	13.8	0.75	9.00	1.9	1.7	3.4	100
DP2210BS	22-16	0.5--1.5	6.00	5	14.8	0.75	10.00	1.9	1.7	3.4	100
DP2212BS	22-16	0.5--1.5	6.00	5	16.8	0.75	12.00	1.9	1.7	3.4	100
DP1609BS	16-14	1.5-2.5	6.00	5	13.8	0.8	9.00	1.9	2.3	4	100
DP1610BS	16-14	1.5-2.5	6.00	5	14.8	0.8	10.00	1.9	2.3	4	100
DP1612BS	16-14	1.5-2.5	6.00	5	16.8	0.8	12.00	1.9	2.3	4	100
DP1613BS	16-14	1.5-2.5	6.00	5	17.8	0.8	13.00	1.9	2.3	4	100
DP1614BS	16-14	1.5-2.5	6.00	5	18.8	0.8	14.00	1.9	2.3	4	100
DP1615BS	16-14	1.5-2.5	6.00	5	19.8	0.8	15.00	1.9	2.3	4	100
DP1616BS	16-14	1.5-2.5	6.00	5	21	0.8	16.00	1.9	2.3	4	100
DP1210BS	12-10	2.5--6	7.00	6	16	1	10.00	2.8	3.4	5.5	100
DP1212BS	12-10	2.5--6	7.00	6	19	1	14.00	2.8	3.4	5.5	100
DP1213BS	12-10	2.5--6	7.00	6	18	1	12.00	2.8	3.4	5.5	100
DP0812BS	8	10	9.00	8	22	1.1	14.00	4.3	4.5	6.9	100
DP0613BS	6	16	11.00	10	26	1.2	16.00	5.5	5.8	8.4	100
DP0415BS	4	25	14.50	13.5	33.5	1.2	20.00	6.8	7	9.5	100
DP0220BS	2	35	17.00	16	40.5	1.5	24.50	8	8.4	11.8	100
DP1020BS	1/0	50	20.00	19	45	1.8	26.00	9.5	9.6	13.6	100
DP2025BS	2/0	70	25.50	24	55	2	31.00	11	11.4	15.8	100
DP3025BS	3/0	95	25.50	24	55	2.5	25.00	12.5	13.5	18.9	100
DP4034BS	4/0	120	25.50	24	58	2.7	34.00	15	15	21	100
DP2537BS	250/350	150	29.00	27	62	3.3	37.00	16.5	16.5	23.1	100
DP3138BS	300/350	185	37.00	35	70	3.5	38.00	19	19	26	100
DP4144BS	400/450	240	42.00	40	82	4	44.00	21	21	29	100
DP5145BS	500/600	300	46.00	44	86	4.3	45.00	23.5	23.5	31.7	100
DP6148BS	600/750	400	50.00	48	93	4.5	48.00	27	27	36.2	100