



Application for Cable Size				Dimension(mm)									Std. Pkg.
Cat. Nos	Stud(Metric)	mm²	A.W.G Stripped Length(mm)	E	L	T	F	W	d1	d2	D		
DSN2203BS	3	0.5-1.5	20-16	7.00	10.7	19.3	0.75	16.00	6	1.7	3.2	3.9	100
DSN2235BS	3.5	0.5-1.5	20-16	7.00	10.7	19.3	0.75	16.00	6	1.7	3.7	3.9	100
DSN2204BS	4	0.5-1.5	20-16	7.00	10.7	21.3	0.75	17.00	6.8	1.7	4.3	3.9	100
DSN2204LBS	4	0.5-1.5	20-16	7.00	10.7	21.3	0.75	17.00	8	1.7	4.3	3.9	100
DSN2205BS	5	0.5-1.5	20-16	7.00	10.7	23.3	0.75	18.00	10	1.7	5.3	3.9	100
DSN2206BS	6	0.5-1.5	20-16	7.00	10.7	25.9	0.75	20.00	11	1.7	6.4	3.9	100
DSN1603BS	3	1.5-2.5	16-13	7.00	10.7	19.6	0.8	18.00	5.5	2.3	3.2	4.5	100
DSN1635BS	3.5	1.5-2.5	16-13	7.00	10.7	19.6	0.8	16.00	6	2.3	3.7	4.5	100
DSN1604BS	4	1.5-2.5	16-13	7.00	10.7	21.6	0.8	17.00	6.8	2.3	4.3	4.5	100
DSN1604LBS	4	1.5-2.5	16-13	7.00	10.7	21.6	0.8	17.00	8	2.3	4.3	4.5	100
DSN1605BS	5	1.5-2.5	16-13	7.00	10.7	24.6	0.8	19.00	10	2.3	5.3	4.5	100
DSN1606BS	6	1.5-2.5	16-13	7.00	10.7	27.1	0.8	21.00	11	2.3	6.4	4.5	100
DSN1204BS	4	4-6	12-10	8.50	12.7	23.9	1	21.00	8	3.4	4.3	6.4	100
DSN1205BS	5	4-6	12-10	8.50	12.7	26.1	1	22.00	10	3.4	5.3	6.4	100
DSN1206BS	6	4-6	12-10	8.50	12.7	27.9	1	23.00	11	3.4	6.4	6.4	100
DSN1208BS	8	4-6	12-10	8.50	12.7	32.3	1	26.00	14	3.4	8.4	6.4	100
DSN1210BS	10	4-6	12-10	8.50	12.7	35.3	1	28.00	18	3.4	10.5	6.4	100