



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
DSV2203BS	3	0.5-1.5	20-16	6.5-7.0	10	18.6	0.75	16.00	6	1.7	3.2	4.3	100
DSV2235BS	3.5	0.5-1.5	20-16	6.5-7.0	10	18.6	0.75	16.00	6	1.7	3.7	4.3	100
DSV2204BS	4	0.5-1.5	20-16	6.5-7.0	10	20.6	0.75	17.00	6.8	1.7	4.3	4.3	100
DSV2204LBS	4	0.5-1.5	20-16	6.5-7.0	10	20.6	0.75	17.00	8	1.7	4.3	4.3	100
DSV2205BS	5	0.5-1.5	20-16	6.5-7.0	10	22.6	0.75	18.00	10	1.7	5.3	4.3	100
DSV2206BS	6	0.5-1.5	20-16	6.5-7.0	10	25.2	0.75	20.00	11	1.7	6.4	4.3	100
DSV1603BS	3	1.5-2.5	16-13	6.5-7.0	10	18.6	0.8	18.00	5.5	2.3	3.2	4.8	100
DSV1635BS	3.5	1.5-2.5	16-13	6.5-7.0	10	18.6	0.8	16.00	6	2.3	3.7	4.8	100
DSV1604BS	4	1.5-2.5	16-13	6.5-7.0	10	20.6	0.8	17.00	6.8	2.3	4.3	4.8	100
DSV1604LBS	4	1.5-2.5	16-13	6.5-7.0	10	20.6	0.8	17.00	8	2.3	4.3	4.8	100
DSV1605BS	5	1.5-2.5	16-13	6.5-7.0	10	23.6	0.8	19.00	10	2.3	5.3	4.8	100
DSV1606BS	6	1.5-2.5	16-13	6.5-7.0	10	26.2	0.8	21.00	11	2.3	6.4	4.8	100
DSV1204BS	4	4-6	12-10	7.0-8.0	13	24.2	1	21.00	8	3.4	4.3	6.7	100
DSV1205BS	5	4-6	12-10	7.0-8.0	13	26.4	1	22.00	10	3.4	5.3	6.7	100
DSV1206BS	6	4-6	12-10	7.0-8.0	13	28.2	1	23.00	11	3.4	6.4	6.7	100
DSV1208BS	8	4-6	12-10	7.0-8.0	13	32.6	1	26.00	14	3.4	8.4	6.7	100
DSV1210BS	10	4-6	12-10	7.0-8.0	13	35.6	1	28.00	18	3.4	10.5	6.7	100