



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
RV2232BS	3	0.5-1.5	22-16	6.5-7.0	10	17.5	0.75	4.80	5.5	1.7	3.2	4.3	100
RV2237SBS	3.5	0.5-1.5	22-16	6.5-7.0	10	17.5	0.75	4.80	5.5	1.7	3.7	4.3	100
RV2237MBS	3.5	0.5-1.5	22-16	6.5-7.0	10	19.4	0.75	6.30	6.6	1.7	3.7	4.3	100
RV2237LBS	3.5	0.5-1.5	22-16	6.5-7.0	10	20.8	0.75	7.00	8	1.7	3.7	4.3	100
RV2204SBS	4	0.5-1.5	22-16	6.5-7.0	10	19.4	0.75	6.30	6.6	1.7	4.3	4.3	100
RV2204LBS	4	0.5-1.5	22-16	6.5-7.0	10	20.8	0.75	7.00	8	1.7	4.3	4.3	100
RV2205BS	5	0.5-1.5	22-16	6.5-7.0	10	20.8	0.75	7.00	8	1.7	5.3	4.3	100
RV2205LBS	5	0.5-1.5	22-16	6.5-7.0	10	26.7	0.75	11.00	11.8	1.7	5.3	4.3	100
RV2206BS	6	0.5-1.5	22-16	6.5-7.0	10	26.7	0.75	11.00	11.8	1.7	6.4	4.3	100
RV2208BS	8	0.5-1.5	22-16	6.5-7.0	10	26.7	0.75	11.00	11.8	1.7	8.4	4.3	100
RV2210BS	10	0.5-1.5	22-16	6.5-7.0	10	30.5	0.75	13.90	13.6	1.7	10.5	4.3	100
RV1632BS	3	1.5-2.5	16-14	6.5-7.0	10	17.8	0.8	4.70	6.6	2.3	3.2	4.8	100
RV1637SBS	3.5	1.5-2.5	16-14	6.5-7.0	10	17.8	0.8	4.70	6.6	2.3	3.7	4.8	100
RV1637MBS	3.5	1.5-2.5	16-14	6.5-7.0	10	19.5	0.8	6.30	6.6	2.3	3.7	4.8	100
RV1637LBS	3.5	1.5-2.5	16-14	6.5-7.0	10	21.8	0.8	7.40	8.5	2.3	3.7	4.8	100
RV1604SBS	4	1.5-2.5	16-14	6.5-7.0	10	19.5	0.8	6.30	6.6	2.3	4.3	4.8	100
RV1604LBS	4	1.5-2.5	16-14	6.5-7.0	10	21.8	0.8	7.80	8.5	2.3	4.3	4.8	100
RV1605SBS	5	1.5-2.5	16-14	6.5-7.0	10	21.8	0.8	7.80	8.5	2.3	5.3	4.8	100
RV1605LBS	5	1.5-2.5	16-14	6.5-7.0	10	22	0.8	7.30	9.6	2.3	5.3	4.8	100
RV1606BS	6	1.5-2.5	16-14	6.5-7.0	10	26.9	0.8	11.00	12	2.3	6.4	4.8	100
RV1608BS	8	1.5-2.5	16-14	6.5-7.0	10	26.9	0.8	11.00	12	2.3	8.4	4.8	100
RV1610BS	10	1.5-2.5	16-14	6.5-7.0	10	30.5	0.8	13.60	13.6	2.3	10.5	4.8	100
RV1237BS	3.5	4-6	12-10	7.0-8.0	13	22.7	1	6.10	7.2	3.4	3.7	6.7	100
RV1204SBS	4	4-6	12-10	7.0-8.0	13	22.7	1	6.10	7.2	3.4	4.3	6.7	100
RV1204LBS	4	4-6	12-10	7.0-8.0	13	26	1	8.30	9.5	3.4	4.3	6.7	100
RV1205BS	5	4-6	12-10	7.0-8.0	13	26	1	8.30	9.5	3.4	5.3	6.7	100
RV1206BS	6	4-6	12-10	7.0-8.0	13	29.5	1	10.50	12	3.4	6.4	6.7	100
RV1208BS	8	4-6	12-10	7.0-8.0	13	34	1	13.50	15	3.4	8.4	6.7	100
RV1210BS	10	4-6	12-10	7.0-8.0	13	34	1	13.50	15	3.4	10.5	6.7	100
RV1212BS	12	4-6	12-10	7.0-8.0	13	38.6	1	16.00	19.2	3.4	13	6.7	100