



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
BV2209BS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	18.8	0.75	9.00	2.8	1.7	2.8	4.3	100
BV2210BS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	19.8	0.75	10.00	2.3	1.7	2.3	4.3	100
BV2211BS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	20.8	0.75	11.00	3	1.7	3	4.3	100
BV2213BS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	22.8	0.75	13.00	2.4	1.7	2.4	4.3	100
BV2214BS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	23.8	0.75	14.00	2.4	1.7	2.4	4.3	100
BV2218BS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	27.8	0.75	18.00	2.2	1.7	2.2	4.3	100
BV2218SBS	0.5-1.5	0.5-1.5	22-16	6.5-7.0	10	27.8	0.75	18.00	2	1.7	2	4.3	100
BV1609BS	1.5-2.5	1.5-2.5	16-14	6.5-7.0	10	18.8	0.8	9.00	2.8	2.3	2.8	4.8	100
BV1610BS	1.5-2.5	1.5-2.5	16-14	6.5-7.0	10	19.8	0.8	10.00	2.3	2.3	2.3	4.8	100
BV1613BS	1.5-2.5	1.5-2.5	16-14	6.5-7.0	10	22.8	0.8	13.00	2.4	2.3	2.4	4.8	100
BV1614BS	1.5-2.5	1.5-2.5	16-14	6.5-7.0	10	23.8	0.8	14.00	2.4	2.3	2.4	4.8	100
BV1618SBS	1.5-2.5	1.5-2.5	16-14	6.5-7.0	10	27.8	0.8	18.00	2	2.3	2	4.8	100
BV1618BS	1.5-2.5	1.5-2.5	16-14	6.5-7.0	10	27.8	0.8	18.00	2.2	2.3	2.2	4.8	100
BV1210BS	4-6	4-6	12-10	7.5-8.0	13	23	1	10.00	2.8	3.4	2.8	6.7	100
BV1214BS	4-6	4-6	12-10	7.5-8.0	13	27	1	14.00	4.5	3.4	4.5	6.7	100
BV1214SBS	4-6	4-6	12-10	7.5-8.0	13	27	1	14.00	4	3.4	4	6.7	100
BV1218BS	4-6	4-6	12-10	7.5-8.0	13	31	1	18.00	4.5	3.4	4.5	6.7	100
BV1218SBS	4-6	4-6	12-10	7.5-8.0	13	31	1	18.00	2	3.4	2	6.7	100