




Application for Cable Size				Dimension(mm)									Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
R2232	3	0.5-1.5	22-16	6.00	5	12.5	0.75	4.80	5.5	1.7	3.2	3.4	100
R2237S	3.5	0.5-1.5	22-16	6.00	5	12.5	0.75	4.80	5.5	1.7	3.7	3.4	100
R2237M	3.5	0.5-1.5	22-16	6.00	5	14.4	0.75	6.30	6.6	1.7	3.7	3.4	100
R2237L	3.5	0.5-1.5	22-16	6.00	5	15.8	0.75	7.00	8	1.7	3.7	3.4	100
R2204S	4	0.5-1.5	22-16	6.00	5	14.4	0.75	6.30	6.6	1.7	4.3	3.4	100
R2204L	4	0.5-1.5	22-16	6.00	5	15.8	0.75	7.00	8	1.7	4.3	3.4	100
R2205	5	0.5-1.5	22-16	6.00	5	15.8	0.75	7.00	8	1.7	5.3	3.4	100
R2205L	5	0.5-1.5	22-16	6.00	5	21.7	0.75	11.00	11.8	1.7	5.3	3.4	100
R2206	6	0.5-1.5	22-16	6.00	5	21.7	0.75	11.00	11.8	1.7	6.4	3.4	100
R2208	8	0.5-1.5	22-16	6.00	5	21.7	0.75	11.00	11.8	1.7	8.4	3.4	100
R2210	10	0.5-1.5	22-16	6.00	5	25.5	0.75	13.90	13.6	1.7	10.5	3.4	100
R1632	3	1.5-2.5	16-14	6.00	5	12.8	0.8	4.70	6.6	2.3	3.2	4	100
R1637S	3.5	1.5-2.5	16-14	6.00	5	12.8	0.8	4.70	6.6	2.3	3.7	4	100
R1637M	3.5	1.5-2.5	16-14	6.00	5	14.5	0.8	6.30	6.6	2.3	3.7	4	100
R1637L	3.5	1.5-2.5	16-14	6.00	5	16.8	0.8	7.40	8.5	2.3	3.7	4	100
R1604S	4	1.5-2.5	16-14	6.00	5	14.5	0.8	6.30	6.6	2.3	4.3	4	100
R1604L	4	1.5-2.5	16-14	6.00	5	16.8	0.8	7.80	8.5	2.3	4.3	4	100
R1605S	5	1.5-2.5	16-14	6.00	5	16.8	0.8	7.80	8.5	2.3	5.3	4	100
R1605L	5	1.5-2.5	16-14	6.00	5	17	0.8	7.30	9.6	2.3	5.3	4	100
R1606	6	1.5-2.5	16-14	6.00	5	21.9	0.8	11.00	12	2.3	6.4	4	100
R1608	8	1.5-2.5	16-14	6.00	5	21.9	0.8	11.00	12	2.3	8.4	4	100
R1610	10	1.5-2.5	16-14	6.00	5	25.5	0.8	13.60	13.6	2.3	10.5	4	100
R1237	3.7	4-6	12-10	7.00	6	15.7	1	6.10	7.2	3.4	3.7	5.5	100
R1204S	4	4-6	12-10	7.00	6	15.7	1	6.10	7.2	3.4	4.3	5.5	100
R1204L	4	4-6	12-10	7.00	6	19	1	8.30	9.5	3.4	4.3	5.5	100
R1205	5	4-6	12-10	7.00	6	19	1	8.30	9.5	3.4	5.3	5.5	100
R1206	6	4-6	12-10	7.00	6	22.5	1	10.50	12	3.4	6.4	5.5	100
R1208	8	4-6	12-10	7.00	6	27	1	13.50	15	3.4	8.4	5.5	100
R1210	10	4-6	12-10	7.00	6	27	1	13.50	15	3.4	10.5	5.5	100
R1212	12	4-6	12-10	7.00	6	31.6	1	16.00	19.2	3.4	13	5.5	100
R0837	3.5	8	8	9.50	8.5	21.5	1.2	9.30	8	4.5	3.7	7.2	100
R0804S	4	8	8	9.50	8.5	21.5	1.2	9.30	8	4.5	4.3	7.2	100
R0804M	4	8	8	9.50	8.5	23.8	1.2	10.50	8.8	4.5	4.3	7.2	100
R0804L	4	8	8	9.50	8.5	23.8	1.2	9.30	12	4.5	4.3	7.2	100
R0805S	5	8	8	9.50	8.5	23.8	1.2	10.50	8.8	4.5	5.3	7.2	100
R0805M	5	8	8	9.50	8.5	23.8	1.2	9.30	12	4.5	5.3	7.2	100
R0805L	5	8	8	9.50	8.5	29.8	1.2	13.80	15	4.5	5.3	7.2	100
R0806S	6	8	8	9.50	8.5	23.8	1.2	9.30	12	4.5	6.4	7.2	100
R0806L	6	8	8	9.50	8.5	29.8	1.2	13.80	15	4.5	6.4	7.2	100
R0808	8	8	8	9.50	8.5	29.8	1.2	13.80	15	4.5	8.4	7.2	100
R0810	10	8	8	9.50	8.5	29.8	1.2	13.80	15	4.5	10.5	7.2	100
R0604	4	14	6	11.50	10.5	29.8	1.5	13.30	12	5.8	4.3	9	100
R0605	5	14	6	11.50	10.5	29.8	1.5	13.30	12	5.8	5.3	9	100
R0606S	6	14	6	11.50	10.5	29.8	1.5	13.30	12	5.8	6.4	9	100
R0606L	6	14	6	11.50	10.5	32.5	1.5	14.20	16	5.8	6.4	9	100
R0608	8	14	6	11.50	10.5	32.5	1.5	14.20	16	5.8	8.4	9	100
R0610	10	14	6	11.50	10.5	32.5	1.5	14.20	16	5.8	10.5	9	100
R0612	12	14	6	11.50	10.5	41	1.5	19.80	22	5.8	13	9	100
R0404	4	22	4	13.00	12	33.2	1.7	15.10	12.2	7.7	4.3	11.5	100
R0405S	5	22	4	13.00	12	33.2	1.7	15.10	12.2	7.7	5.3	11.5	100



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
R0405L	5	22	4	13.00	12	33.5	1.7	13.50	16.5	7.7	5.3	11.5	100
R0406S	6	22	4	13.00	12	33.2	1.7	15.10	12.2	7.7	6.4	11.5	100
R0406L	6	22	4	13.00	12	33.5	1.7	13.50	16.5	7.7	6.4	11.5	100
R0408	8	22	4	13.00	12	33.5	1.7	13.50	16.5	7.7	8.4	11.5	100
R0410	10	22	4	13.00	12	33.5	1.7	13.50	16.5	7.7	10.5	11.5	100
R0412	12	22	4	13.00	12	42.5	1.7	19.80	22	7.7	13	11.5	100
R0205	5	38	2	15.00	14	39	1.8	17.40	15.3	9.4	5.3	13.3	100
R0206S	6	38	2	15.00	14	39	1.8	17.40	15.3	9.4	6.4	13.3	100
R0206L	6	38	2	15.00	14	42.7	1.8	17.70	22	9.4	6.4	13.3	100
R0208S	8	38	2	15.00	14	39	1.8	17.40	15.3	9.4	8.4	13.3	100
R0208L	8	38	2	15.00	14	42.7	1.8	17.70	22	9.4	8.4	13.3	100
R0210S	10	38	2	15.00	14	39	1.8	17.40	15.3	9.4	10.5	13.3	100
R0210L	10	38	2	15.00	14	42.7	1.8	17.70	22	9.4	10.5	13.3	100
R0211	11	38	2	15.00	14	42.7	1.8	17.70	22	9.4	11.5	13.3	100
R0212	12	38	2	15.00	14	42.7	1.8	17.70	22	9.4	13	13.3	100
R1006	6	60	1/0	19.50	18	49.7	1.8	20.70	22	11.4	6.4	15.4	100
R1008	8	60	1/0	19.50	18	49.7	1.8	20.70	22	11.4	8.4	15.4	100
R1010	10	60	1/0	19.50	18	49.7	1.8	20.70	22	11.4	10.5	15.4	100
R1011	11	60	1/0	19.50	18	49.7	1.8	20.70	22	11.4	11.5	15.4	100
R1012	12	60	1/0	19.50	18	49.7	1.8	20.70	22	11.4	13	15.4	100
R1013	13	60	1/0	19.50	18	49.7	1.8	20.70	22	11.4	14	15.4	100
R1014	14	60	1/0	19.50	18	57.5	1.8	23.50	32	11.4	15	15.4	100
R1016	16	60	1/0	19.50	18	57.5	1.8	23.50	32	11.4	17	15.4	100
R1018	18	60	1/0	19.50	18	57.5	1.8	23.50	32	11.4	19	15.4	100
R1020	20	60	1/0	19.50	18	57.5	1.8	23.50	32	11.4	21	15.4	100
R1022	22	60	1/0	19.50	18	57.5	1.8	23.50	32	11.4	23	15.4	100
R2006	6	70	2/0	19.50	18	50	2	20.00	24	13.3	6.4	17.5	100
R2008	8	70	2/0	19.50	18	50	2	20.00	24	13.3	8.4	17.5	100
R2010	10	70	2/0	19.50	18	50	2	20.00	24	13.3	10.5	17.5	100
R2011	11	70	2/0	19.50	18	50	2	20.00	24	13.3	11.5	17.5	100
R2012	12	70	2/0	19.50	18	50	2	20.00	24	13.3	13	17.5	100
R2013	13	70	2/0	19.50	18	50	2	20.00	24	13.3	14	17.5	100
R2014	14	70	2/0	19.50	18	61	2	26.00	32	13.3	15	17.5	100
R2016	16	70	2/0	19.50	18	61	2	26.00	32	13.3	17	17.5	100
R2018	18	70	2/0	19.50	18	61	2	26.00	32	13.3	19	17.5	100
R2020	20	70	2/0	19.50	18	61	2	26.00	32	13.3	21	17.5	100
R2022	22	70	2/0	19.50	18	61	2	26.00	32	13.3	23	17.5	100
R3006	6	80	3/0	21.00	20	54.2	2.2	20.70	27	14.5	6.4	19.5	100
R3008	8	80	3/0	21.00	20	54.2	2.2	20.70	27	14.5	8.4	19.5	100
R3010	10	80	3/0	21.00	20	54.2	2.2	20.70	27	14.5	10.4	19.5	100
R3010L	10	80	3/0	21.00	20	68	2.2	32.00	32	14.5	10.4	19.5	100
R3011	11	80	3/0	21.00	20	54.2	2.2	20.70	27	14.5	11.5	19.5	100
R3012	12	80	3/0	21.00	20	54.2	2.2	20.70	27	14.5	13	19.5	100
R3012L	12	80	3/0	21.00	20	68	2.2	32.00	32	14.5	13	19.5	100
R3013	13	80	3/0	21.00	20	54.2	2.2	20.70	27	14.5	14	19.5	100
R3014	14	80	3/0	21.00	20	68	2.2	32.00	32	14.5	15	19.5	100
R3016	16	80	3/0	21.00	20	68	2.2	32.00	32	14.5	17	19.5	100
R3018	18	80	3/0	21.00	20	68	2.2	32.00	32	14.5	19	19.5	100
R3020	20	80	3/0	21.00	20	68	2.2	32.00	32	14.5	21	19.5	100
R3022	22	80	3/0	21.00	20	68	2.2	32.00	32	14.5	23	19.5	100



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
R4006	6	100	4/0	22.50	21	55.6	2.6	20.40	28.5	16.4	6.4	22.1	100
R4008	8	100	4/0	22.50	21	55.6	2.6	20.40	28.5	16.4	8.4	22.1	100
R4010	10	100	4/0	22.50	21	55.6	2.6	20.40	28.5	16.4	10.4	22.1	100
R4010L	10	100	4/0	22.50	21	69	2.6	32.00	32	16.4	10.4	22.1	100
R4011	11	100	4/0	22.50	21	55.6	2.6	20.40	28.5	16.4	11.5	22.1	100
R4012	12	100	4/0	22.50	21	55.6	2.6	20.40	28.5	16.4	13	22.1	100
R4012L	12	100	4/0	22.50	21	69	2.6	32.00	32	16.4	13	22.1	100
R4014	14	100	4/0	22.50	21	69	2.6	32.00	32	16.4	15	22.1	100
R4016	16	100	4/0	22.50	21	69	2.6	32.00	32	16.4	17	22.1	100
R4018	18	100	4/0	22.50	21	69	2.6	32.00	32	16.4	19	22.1	100
R4020	20	100	4/0	22.50	21	69	2.6	32.00	32	16.4	21	22.1	100
R4022	22	100	4/0	22.50	21	69	2.6	32.00	32	16.4	23	22.1	100
R2508	8	150	250/300	28.50	27	68	3.2	23.00	36	19.5	8.4	26.2	100
R2508L	8	150	250/300	28.50	27	81	3.2	36.00	36	19.5	8.4	26.2	100
R2510	10	150	250/300	28.50	27	68	3.2	23.00	36	19.5	10.5	26.2	100
R2510L	10	150	250/300	28.50	27	81	3.2	36.00	36	19.5	10.5	26.2	100
R2511	11	150	250/300	28.50	27	68	3.2	23.00	36	19.5	11.5	26.2	100
R2512	12	150	250/300	28.50	27	68	3.2	23.00	36	19.5	13	26.2	100
R2512L	12	150	250/300	28.50	27	81	3.2	36.00	36	19.5	13	26.2	100
R2514	14	150	250/300	28.50	27	68	3.2	23.00	36	19.5	15	26.2	100
R2516	16	150	250/300	28.50	27	68	3.2	23.00	36	19.5	17	26.2	100
R2516L	16	150	250/300	28.50	27	81	3.2	36.00	36	19.5	17	26.2	100
R2518	18	150	250/300	28.50	27	81	3.2	36.00	36	19.5	19	26.2	100
R2520	20	150	250/300	28.50	27	81	3.2	36.00	36	19.5	21	26.2	100
R2522	22	150	250/300	28.50	27	81	3.2	36.00	36	19.5	23	26.2	100
R2524	24	150	250/300	28.50	27	81	3.2	36.00	36	19.5	25	26.2	100
R2527	27	150	250/300	28.50	27	81	3.2	36.00	36	19.5	28	26.2	100
R3106	6	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	6.4	28.2	100
R3108	8	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	8.4	28.2	100
R3110	10	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	10.5	28.2	100
R3111	11	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	11.5	28.2	100
R3112	12	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	13	28.2	100
R3112L	12	180	300/350	30.00	28.5	86.6	3.5	39.00	38.5	21	13	28.2	100
R3114	14	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	15	28.2	100
R3116	16	180	300/350	30.00	28.5	69	3.5	24.50	38.5	21	17	28.2	100
R3118	18	180	300/350	30.00	28.5	86.6	3.5	39.00	38.5	21	19	28.2	100
R3120	20	180	300/350	30.00	28.5	86.6	3.5	39.00	38.5	21	21	28.2	100
R3122	22	180	300/350	30.00	28.5	86.6	3.5	39.00	38.5	21	23	28.2	100
R3124	24	180	300/350	30.00	28.5	86.6	3.5	39.00	38.5	21	25	28.2	100
R3127	27	180	300/350	30.00	28.5	86.6	3.5	39.00	38.5	21	28	28.2	100
R4108	8	200	400/450	33.00	31.5	72	4	24.50	44	24	8.4	32.2	100
R4108L	8	200	400/450	33.00	31.5	91	4	37.50	44	24	8.4	32.2	100
R4110	10	200	400/450	33.00	31.5	72	4	24.50	44	24	10.5	32.2	100
R4111	11	200	400/450	33.00	31.5	72	4	24.50	44	24	11.5	32.2	100
R4112	12	200	400/450	33.00	31.5	72	4	24.50	44	24	13	32.2	100
R4112L	12	200	400/450	33.00	31.5	91	4	37.50	44	24	13	32.2	100
R4114	14	200	400/450	33.00	31.5	72	4	24.50	44	24	15	32.2	100
R4116	16	200	400/450	33.00	31.5	72	4	24.50	44	24	17	32.2	100
R4116L	16	200	400/450	33.00	31.5	91	4	37.50	44	24	17	32.2	100
R4118	18	200	400/450	33.00	31.5	91	4	37.50	44	24	19	32.2	100



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
R4120	20	200	400/450	33.00	31.5	91	4	37.50	44	24	21	32.2	100
R4122	22	200	400/450	33.00	31.5	91	4	37.50	44	24	23	32.2	100
R4124	24	200	400/450	33.00	31.5	91	4	37.50	44	24	25	32.2	100
R4127	27	200	400/450	33.00	31.5	91	4	37.50	44	24	28	32.2	100
R5108	8	325	500/600	37.50	35.5	88	4.3	33.50	50	28	8.4	37.6	100
R5110	10	325	500/600	37.50	35.5	88	4.3	33.50	50	28	10.5	37.6	100
R5111	11	325	500/600	37.50	35.5	88	4.3	33.50	50	28	11.5	37.6	100
R5112	12	325	500/600	37.50	35.5	88	4.3	33.50	50	28	13	37.6	100
R5112L	12	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	13	37.6	100
R5114	14	325	500/600	37.50	35.5	94.25	4.3	33.50	50.5	28	15	37.6	100
R5116	16	325	500/600	37.50	35.5	94.25	4.3	33.50	50.5	28	17	37.6	100
R5116L	16	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	17	37.6	100
R5118	18	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	19	37.6	100
R5120	20	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	21	37.6	100
R5122	22	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	23	37.6	100
R5124	24	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	25	37.6	100
R5127	27	325	500/600	37.50	35.5	105.7	4.3	45.00	50.5	28	28	37.6	100