



Application for Cable Size					Dimension(mm)								Std. Pkg.
Cat. Nos	Stud(Metric)	mm ²	A.W.G	Stripped Length(mm)	E	L	T	F	W	d1	d2	D	
S2232	3	0.5-1.5	22-16	6.00	5	16	0.75	6.50	5.7	1.7	3.3	3.4	100
S2237S	3.5	0.5-1.5	22-16	6.00	5	16	0.75	6.50	5.7	1.7	3.8	3.4	100
S2237L	3.5	0.5-1.5	22-16	6.00	5	16	0.75	6.50	6.4	1.7	3.8	3.4	100
S2204S	4	0.5-1.5	22-16	6.00	5	16	0.75	6.50	6.4	1.7	4.4	3.4	100
S2204M	4	0.5-1.5	22-16	6.00	5	16	0.75	6.50	7.2	1.7	4.4	3.4	100
S2237LL	3.5	0.5-1.5	22-16	6.00	5	16	0.75	6.50	7.2	1.7	3.8	3.4	100
S2204L	4	0.5-1.5	22-16	6.00	5	16	0.75	6.50	8.1	1.7	4.4	3.4	100
S2205S	5	0.5-1.5	22-16	6.00	5	16	0.75	6.50	8.1	1.7	5.4	3.4	100
S2205L	5	0.5-1.5	22-16	6.00	5	16	0.75	6.50	9.5	1.7	5.4	3.4	100
S2206S	6	0.5-1.5	22-16	6.00	5	16	0.75	6.50	9.5	1.7	6.6	3.4	100
S2206L	6	0.5-1.5	22-16	6.00	5	22	0.75	11.00	12	1.7	6.6	3.4	100
S1632	3	1.5-2.5	16-14	6.00	5	16	0.8	6.50	5.7	2.3	3.3	4	100
S1637S	3.5	1.5-2.5	16-14	6.00	5	16	0.8	6.50	5.7	2.3	3.8	4	100
S1637L	3.5	1.5-2.5	16-14	6.00	5	16	0.8	6.50	6	2.3	3.8	4	100
S1604S	4	1.5-2.5	16-14	6.00	5	16	0.8	6.50	6.4	2.3	4.4	4	100
S1637LL	3.5	1.5-2.5	16-14	6.00	5	16	0.8	6.50	7.2	2.3	3.8	4	100
S1604M	4	1.5-2.5	16-14	6.00	5	16	0.8	6.50	7.2	2.3	4.4	4	100
S1604L	4	1.5-2.5	16-14	6.00	5	16	0.8	6.50	8.1	2.3	4.4	4	100
S1605S	5	1.5-2.5	16-14	6.00	5	16	0.8	6.50	8.1	2.3	5.4	4	100
S1605L	5	1.5-2.5	16-14	6.00	5	16	0.8	6.50	9.3	2.3	5.4	4	100
S1606S	6	1.5-2.5	16-14	6.00	5	16	0.8	6.50	9.3	2.3	6.6	4	100
S1606L	6	1.5-2.5	16-14	6.00	5	22	0.8	11.00	12	2.3	6.6	4	100
S1437	3.5	2.5-4	14-12	7.00	6	18.3	1	7.00	8	3	3.8	5	100
S1404	4	2.5-4	14-12	7.00	6	18.3	1	7.00	8	3	4.4	5	100
S1405	5	2.5-4	14-12	7.00	6	18.3	1	7.00	8	3	5.4	5	100
S1406	6	2.5-4	14-12	7.00	6	21.5	1	12.10	12	3	6.5	5	100
S1237	3.5	4-6	12-10	7.00	6	18.5	1	7.00	8.3	3.4	3.8	5.5	100
S1204S	4	4-6	12-10	7.00	6	18.5	1	7.00	8.3	3.4	4.4	5.5	100
S1204L	4	4-6	12-10	7.00	6	18.5	1	7.00	9	3.4	4.4	5.5	100
S1205	5	4-6	12-10	7.00	6	18.5	1	7.00	9	3.4	5.4	5.5	100
S1206S	6	4-6	12-10	7.00	6	18.5	1	7.00	9	3.4	6.6	5.5	100
S1206L	6	4-6	12-10	7.00	6	24.5	1	12.00	12	3.4	6.6	5.5	100
S1208	8	4-6	12-10	7.00	6	23.5	1	11.50	14	3.4	8.5	5.5	100
S1237S	3.5	4-6	12-10	7.00	6	17.4	1	7.50	7.2	3.4	3.8	5.5	100
S1204SS	4	4-6	12-10	7.00	6	17.4	1	7.50	7.2	3.4	4.4	5.5	100
S0805	5	8	8	9.50	8.5	20.8	1.2	8.10	10.5	4.5	5.4	7.2	100
S0806	6	8	8	9.50	8.5	22.5	1.2	8.60	10.8	4.5	6.6	7.2	100
S0606	6	14	6	11.50	10.5	25	1.5	10.70	11	5.8	6.6	9	100
S0608	8	14	6	11.50	10.5	28.5	1.5	10.70	13.8	5.8	8.5	9	100