

Heavy Duty C-Tap for 600V Applications



Cat. Nos	Wire Range		Dimension (in.)			Die Code	Die Color	Std. Pkg.
	Main	Branch	A	B	C			
TC4008	#1	#1	1.29	0.77	0.51	76	Blue	100
TC4008	1/0-#2	1/0-#2	1.29	0.77	0.51	76	Blue	100
TC2508	2/0	2/0-#1	1.45	0.77	0.60	87H	Brown	100
TC2508	3/0	3/0-#3	1.45	0.77	0.60	87H	Brown	100
TC2508	4/0	4/0-#4	1.45	0.77	0.60	87H	Brown	100
TC2508	250 kcmil	#1-#8	1.45	0.77	0.60	87H	Brown	100
TC3108	2/0	2/0-#1	1.68	1.02	0.64	99H	Pink	100
TC3108	3/0	3/0-#2	1.68	1.02	0.64	99H	Pink	100
TC3108	4/0	4/0-#4	1.68	1.02	0.64	99H	Pink	100
TC3108	250 kcmil	3/0-#6	1.68	1.02	0.64	99H	Pink	100
TC3108	300 kcmil	2/0-#8	1.68	1.02	0.64	99H	Pink	100
TC3506	4/0	4/0-2/0	1.70	1.02	0.69	106H	Black	100
TC3506	250 kcmil	250-#1	1.70	1.02	0.69	106H	Black	100
TC3506	300 kcmil	4/0-#4	1.70	1.02	0.69	106H	Black	100
TC3506	350 kcmil	3/0-#6	1.70	1.02	0.69	106H	Black	100
TC5106	250 kcmil	250 kcmil	1.87	1.28	0.82	115H	Yellow	100
TC5106	300 kcmil	300-3/0	1.87	1.28	0.82	115H	Yellow	100
TC5106	350 kcmil	350-1/0	1.87	1.28	0.82	115H	Yellow	100
TC5106	400 kcmil	300-#2	1.87	1.28	0.82	115H	Yellow	100
TC5106	450 kcmil	250-#4	1.87	1.28	0.82	115H	Yellow	100
TC5106	500 kcmil	250-#6	1.87	1.28	0.82	115H	Yellow	100
TC5102	500 kcmil	500-#2	2.19	1.28	0.83	125H	N/A	100
TC7506	750 kcmil	4/0-#6	2.13	2.04	1.00	125H	N/A	100
TC7540	750 kcmil	750-4/0	2.69	2.04	1.31	125H	N/A	100