

COMPRESSION CONNECTORS

Thin Wall C-Tap for 600V Applications



Cat. Nos	Wire Range		Dimension (in.)			Die Color	Std. Pkg.
	Run	Tap	A	B	C		
TC1416	#14	#16-#14	0.34	0.31	0.10	Red	100
TC0812	#8	#12	0.57	0.44	0.14	Blue	100
TC0612	#8	#10-#8	0.60	0.54	0.19	Gray	100
TC0412	#6	#8-#6	1.16	0.64	0.29	Brown	100
TC0312	#5-#4	#6-#5	1.17	0.71	0.26	Green	100
TC0212	#4	#4	1.17	0.76	0.30	Pink	100
TC0112	#3	#4-#3	1.75	0.79	0.34	Black	100
TC1012	#2	#4-#2	1.76	0.90	0.43	Orange	100
TC2012	#1	#2-#1	1.76	0.96	0.42	Purple	100
TC3012	1/0	#1-1/0	1.76	1.10	0.48	Yellow	100
TC1416	#12	#16-#12	0.34	0.31	0.10	Red	100
TC1416	#10	#14	0.34	0.31	0.10	Red	100
TC0812	#10	#10	0.57	0.44	0.14	Blue	100
TC0612	#6	#12-#10	0.60	0.54	0.19	Gray	100
TC0412	#5-#4	#12-#8	1.16	0.64	0.29	Brown	100
TC0312	#3	#12-#6	1.17	0.71	0.26	Green	100
TC0212	#3	#5	1.17	0.76	0.30	Pink	100
TC0212	#2	#12-#6	1.17	0.76	0.30	Pink	100
TC0112	#2	#5-#4	1.75	0.79	0.34	Black	100
TC0112	#1	#12-#5	1.75	0.79	0.34	Black	100
TC1012	#1	#4-#3	1.76	0.90	0.43	Orange	100
TC1012	1/0	#12-#4	1.76	0.90	0.43	Orange	100
TC2012	1/0	#3-#2	1.76	0.96	0.42	Purple	100
TC2012	2/0	#12-#3	1.76	0.96	0.42	Purple	100
TC3012	2/0	#2-#1	1.76	1.10	0.48	Yellow	100
TC3012	3/0	#12-#2	1.76	1.10	0.48	Yellow	100

COMPRESSION CONNECTORS

Heavy Duty C-Tap for 600V Applications



Cat. Nos	Wire Range		Dimension (in.)			Die Code	Die Color	Std. Pkg.
	Main	Branch	A	B	C			
TC4008	#1	#1	1.29	0.77	0.51	76	Blue	100
TC4008	1/0-#2	1/0-#2	1.29	0.77	0.51	76	Blue	100
TC2508	2/0	2/0-#1	1.45	0.77	0.60	87H	Brown	100
TC2508	3/0	3/0-#3	1.45	0.77	0.60	87H	Brown	100
TC2508	4/0	4/0-#4	1.45	0.77	0.60	87H	Brown	100
TC2508	250 kcmil	#1-#8	1.45	0.77	0.60	87H	Brown	100
TC3108	2/0	2/0-#1	1.68	1.02	0.64	99H	Pink	100
TC3108	3/0	3/0-#2	1.68	1.02	0.64	99H	Pink	100
TC3108	4/0	4/0-#4	1.68	1.02	0.64	99H	Pink	100
TC3108	250 kcmil	3/0-#6	1.68	1.02	0.64	99H	Pink	100
TC3108	300 kcmil	2/0-#8	1.68	1.02	0.64	99H	Pink	100
TC3506	4/0	4/0-2/0	1.70	1.02	0.69	106H	Black	100
TC3506	250 kcmil	250-#1	1.70	1.02	0.69	106H	Black	100
TC3506	300 kcmil	4/0-#4	1.70	1.02	0.69	106H	Black	100
TC3506	350 kcmil	3/0-#6	1.70	1.02	0.69	106H	Black	100
TC5106	250 kcmil	250 kcmil	1.87	1.28	0.82	115H	Yellow	100
TC5106	300 kcmil	300-3/0	1.87	1.28	0.82	115H	Yellow	100
TC5106	350 kcmil	350-1/0	1.87	1.28	0.82	115H	Yellow	100
TC5106	400 kcmil	300-#2	1.87	1.28	0.82	115H	Yellow	100
TC5106	450 kcmil	250-#4	1.87	1.28	0.82	115H	Yellow	100
TC5106	500 kcmil	250-#6	1.87	1.28	0.82	115H	Yellow	100
TC5102	500 kcmil	500-#2	2.19	1.28	0.83	125H	N/A	100
TC7506	750 kcmil	4/0-#6	2.13	2.04	1.00	125H	N/A	100
TC7540	750 kcmil	750-4/0	2.69	2.04	1.31	125H	N/A	100