


COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Blue	24
Panduit	-	Blue	-
Burndy	MY29 Y644M	Blue	374
Celestra	-	Blue	-

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL0810	#10	#8 AWG	1.28	0.56	0.41	0.09	0.22	0.17	0.52	—
AL0810-62	#10	#8 AWG	1.42	0.60	0.40	0.13	0.20	0.17	0.62	—
AL0814	1/4	#8 AWG	1.43	0.71	0.44	0.09	0.34	0.17	0.52	—
AL0814-62	1/4	#8 AWG	1.57	0.75	0.43	0.12	0.25	0.17	0.62	—
AL0838	3/8	#8 AWG	1.65	0.93	0.60	0.06	0.44	0.17	0.52	—
AL0856	5/16	#8 AWG	1.63	0.91	0.60	0.06	0.44	0.17	0.52	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Gray	29
Panduit	CT-720 CT-920	Gray	P29
Burndy	Y1MR Y2MR	Gray	8
Celestra	A45	Gray	29

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL0610	#10	#6 AWG	1.56	0.59	0.47	0.15	0.22	0.20	0.72	—
AL0614	1/4	#6 AWG	1.72	0.75	0.47	0.15	0.34	0.20	0.72	—
AL0614-52	1/4	#6 AWG	2.04	0.93	0.48	0.13	0.41	0.20	0.86	—
AL0614-62	1/4	#6 AWG	1.75	0.75	0.47	0.14	0.33	0.20	0.75	—
AL0638	3/8	#6 AWG	1.90	0.93	0.63	0.1	0.44	0.20	0.72	—
AL0638-62	3/8	#6 AWG	2.19	1.19	0.66	0.09	0.44	0.20	0.75	—
AL0656	5/16	#6 AWG	1.88	0.91	0.63	0.1	0.44	0.20	0.72	—
AL0656-52	5/16	#6 AWG	2.18	0.93	0.55	0.11	0.41	0.20	1.00	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Green	37
Panduit	CT-720 CT-1700	Green	P37
Burndy	MY29 Y644M	Green	11
Celestra	A45	Green	37

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL0414	1/4	#4 AWG	1.94	0.75	0.64	0.19	0.34	0.27	0.91	—
AL0414-52	1/4	#4 AWG	2.05	0.72	0.62	0.21	0.34	0.26	1.05	—
AL0414-62	1/4	#4 AWG	1.91	0.75	0.58	0.17	0.33	0.26	0.88	—
AL0438	3/8	#4 AWG	2.12	0.93	0.64	0.19	0.44	0.27	0.91	—
AL0438-52	3/8	#4 AWG	2.20	1.00	0.62	0.21	0.44	0.26	0.92	—
AL0438-62	3/8	#4 AWG	2.10	0.94	0.80	0.12	0.44	0.26	0.88	—
AL0456	5/16	#4 AWG	2.10	0.91	0.64	0.19	0.44	0.27	0.91	—
AL0456-52	5/16	#4 AWG	2.36	1.00	0.62	0.21	0.44	0.26	1.08	—
AL0456-62	5/16	#4 AWG	2.03	0.87	0.80	0.12	0.41	0.26	0.88	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Pink	42
Panduit	CT-720 CT-920	Pink	P42
Burndy	MY29 Y644M	Pink	12
Celestra	A45	Pink	42

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL0212	1/2	#2 AWG	2.57	1.41	0.88	0.15	0.69	0.31	0.86	—
AL0214	1/4	#2 AWG	1.91	0.75	0.72	0.19	0.34	0.31	0.86	—
AL0214-52	1/4	#2 AWG	2.41	1.13	0.71	0.22	0.44	0.31	0.98	—
AL0214-62	1/4	#2 AWG	2.17	0.75	0.85	0.18	0.33	0.31	1.12	—
AL0238	3/8	#2 AWG	2.09	0.93	0.72	0.19	0.44	0.31	0.86	—
AL0238-52	3/8	#2 AWG	2.41	1.13	0.71	0.22	0.44	0.31	0.98	—
AL0238-62	3/8	#2 AWG	2.36	0.94	0.85	0.18	0.44	0.31	1.12	—
AL0256	5/16	#2 AWG	2.07	0.91	0.72	0.19	0.44	0.31	0.86	—
AL0256-52	5/16	#2 AWG	2.41	1.13	0.71	0.22	0.44	0.31	0.98	—
AL0256-62	5/16	#2 AWG	2.30	0.88	0.85	0.18	0.41	0.31	1.12	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Black	45
Panduit	CT-720 CT-920	Black	P45
Burndy	MY29 Y644M	Black	13
Celestra	A45	Black	45

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL0112	1/2	#1 AWG	2.82	1.41	0.88	0.16	0.69	0.37	1.09	—
AL0114	1/4	#1 AWG	2.22	0.81	0.75	0.19	0.34	0.37	1.09	—
AL0114-52	1/4	#1 AWG	2.43	1.13	0.74	0.16	0.44	0.37	0.98	—
AL0114-62	1/4	#1 AWG	1.98	0.75	0.75	0.17	0.33	0.37	0.91	—
AL0138	3/8	#1 AWG	2.34	0.93	0.75	0.19	0.44	0.37	1.09	—
AL0138-52	3/8	#1 AWG	2.43	1.13	0.74	0.16	0.44	0.37	0.98	—
AL0138-62	3/8	#1 AWG	2.42	1.19	0.75	0.17	0.44	0.37	0.91	—
AL0156	5/16	#1 AWG	2.32	0.91	0.75	0.19	0.44	0.37	1.09	—
AL0156-52	5/16	#1 AWG	2.43	1.13	0.74	0.16	0.44	0.37	0.98	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Orange	50
Panduit	CT-720 CT-920	Orange	P50
Burndy	MY29 Y644M	Orange	14
Celestra	A45	Orange	50

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL1012	1/2	1/0 AWG	2.91	1.41	0.94	0.19	0.69	0.41	1.15	—
AL1012-52	1/2	1/0 AWG	2.91	1.26	0.88	0.25	0.63	0.39	1.30	—
AL1012-62	1/2	1/0 AWG	2.74	1.34	0.82	0.21	0.63	0.39	1.05	—
AL1014	1/4	1/0 AWG	2.31	0.81	0.88	0.2	0.34	0.41	1.15	—
AL1038	3/8	1/0 AWG	2.47	0.97	0.88	0.2	0.44	0.41	1.15	—
AL1038-52	3/8	1/0 AWG	2.91	1.26	0.88	0.25	0.63	0.39	1.30	—
AL1038-62	3/8	1/0 AWG	2.58	1.18	0.82	0.21	0.63	0.39	1.05	—
AL1056	5/16	1/0 AWG	2.47	0.97	0.88	0.2	0.44	0.41	1.15	—
AL1056-52	5/16	1/0 AWG	2.91	1.26	0.88	0.25	0.63	0.39	1.30	—
AL1056-62	5/16	1/0 AWG	2.22	0.87	0.82	0.21	0.41	0.39	1.00	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM8	Purple	54
Panduit	CT-720 CT-920	Purple	P54
Burndy	MY29 Y644M	Purple	15
Celestra	A45	Purple	54

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL2012	1/2	2/0 AWG	3.02	1.41	0.97	0.24	0.69	0.46	1.21	—
AL2012-52	1/2	2/0 AWG	2.96	1.26	0.94	0.25	0.63	0.44	1.30	—
AL2012-62	1/2	2/0 AWG	2.93	1.36	0.92	0.23	0.63	0.44	1.17	—
AL2014	1/4	2/0 AWG	2.48	0.87	0.97	0.24	0.34	0.46	1.21	—
AL2038	3/8	2/0 AWG	2.64	1.03	0.97	0.24	0.44	0.46	1.21	—
AL2038-52	3/8	2/0 AWG	3.00	1.29	0.94	0.25	0.63	0.44	1.31	—
AL2038-62	3/8	2/0 AWG	2.75	1.18	0.92	0.23	0.44	0.44	1.17	—
AL2056	5/16	2/0 AWG	2.64	1.03	0.97	0.24	0.44	0.46	1.21	—
AL2058-62	5/8	2/0 AWG	2.93	1.36	0.92	0.23	0.63	0.44	1.17	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	BPLT14	--	60
Panduit	CT-930 CT-940	--	P94
Burndy	PAT750 Y35	--	22
Celestra	A45	--	60

Cat. Nos	Wire Size		Dimension (in.)								Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H		
AL3012	1/2	3/0 AWG	3.30	1.41	1.06	0.24	0.69	0.52	1.39	—	
AL3012-52	1/2	3/0 AWG	3.26	1.26	1.03	0.27	0.63	0.48	1.50	—	
AL3012-62	1/2	3/0 AWG	3.18	1.37	1.04	0.28	0.63	0.48	1.31	—	
AL3014	1/4	3/0 AWG	2.76	0.87	1.06	0.24	0.34	0.52	1.39	—	
AL3038	3/8	3/0 AWG	2.98	1.09	1.06	0.24	0.44	0.52	1.39	—	
AL3038-52	3/8	3/0 AWG	3.26	1.26	1.03	0.27	0.63	0.48	1.50	—	
AL3038-62	3/8	3/0 AWG	2.99	1.18	1.04	0.28	0.44	0.48	1.31	—	
AL3056	5/16	3/0 AWG	2.98	1.09	1.06	0.24	0.44	0.52	1.39	—	

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM6 TBM8	White	66
Panduit	CT-720 CT-920	White	P66
Burndy	Y35 Y45	White	17
Celestra	A45	White	66

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL4012	1/2	4/0 AWG	3.62	1.25	1.21	0.25	0.50	0.60	1.77	—
AL4012-52	1/2	4/0 AWG	3.39	1.35	1.19	0.33	0.63	0.55	1.44	—
AL4012-62	1/2	4/0 AWG	3.35	1.36	1.17	0.3	0.63	0.55	1.39	—
AL4038	3/8	4/0 AWG	3.30	0.93	1.21	0.25	0.38	0.60	1.77	—
AL4038-52	3/8	4/0 AWG	3.39	1.35	1.19	0.33	0.63	0.55	1.44	—
AL4038-62	3/8	4/0 AWG	3.17	1.18	1.17	0.3	0.44	0.55	1.39	—
AL4056	5/16	4/0 AWG	3.25	0.88	1.21	0.25	0.38	0.60	1.77	—
AL4058	5/8	4/0 AWG	4.37	2.00	1.21	0.25	0.75	0.60	1.77	—
AL4058-62	5/8	4/0 AWG	3.51	1.52	1.17	0.3	0.75	0.55	1.39	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM6 TBM8	Red	71
Panduit	CT-720 CT-920	Red	P71
Burndy	Y35 Y45	Red	18
Celestra	A45	Red	71

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL2512	1/2	250 kcmil	3.78	1.25	1.29	0.27	0.50	0.65	1.93	—
AL2512-52	1/2	250 kcmil	3.48	1.32	1.25	0.31	0.63	0.59	1.56	—
AL2512-62	1/2	250 kcmil	3.41	1.36	1.26	0.33	0.63	0.59	1.45	—
AL2538	3/8	250 kcmil	3.46	0.93	1.29	0.27	0.38	0.65	1.93	—
AL2538-52	3/8	250 kcmil	3.48	1.32	1.25	0.31	0.63	0.59	1.56	—
AL2558	5/8	250 kcmil	4.53	2.00	1.29	0.27	0.75	0.65	1.93	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM6 TBM8	Blue	76
Panduit	CT-720 CT-920	Blue	P76
Burndy	Y35 Y45	Blue	19
Celestra	A45	Blue	76

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL3112	1/2	300 Kcmil	3.88	1.25	1.39	0.28	0.50	0.71	1.93	—
AL3112-52	1/2	300 Kcmil	4.27	1.32	1.39	0.36	0.63	0.65	2.25	—
AL3112-62	1/2	300 Kcmil	3.60	1.37	1.38	0.36	—	0.65	1.53	—
AL3138	3/8	300 Kcmil	3.56	0.93	1.39	0.28	0.38	0.71	1.93	—
AL3138-52	3/8	300 Kcmil	4.27	1.32	1.39	0.36	0.63	0.65	2.25	—
AL3138-62	3/8	300 Kcmil	3.60	1.37	1.38	0.36	0.63	0.65	1.53	—
AL3156	5/16	300 Kcmil	3.51	0.88	1.39	0.28	0.38	0.71	1.93	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM8 TBM12	Brown	87
Panduit	CT-720 CT-920	Brown	P87
Burndy	Y35 Y45	Brown	20
Celestra	A45	Brown	87

Cat. Nos	Wire Size		Dimension (in.)							
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	Std. Pkg.
AL3512	1/2	350 Kcmil	4.57	1.25	1.52	0.34	0.50	0.75	2.62	—
AL3512-52	1/2	350 Kcmil	4.27	1.32	1.52	0.39	0.63	0.72	2.25	—
AL3512-62	1/2	350 Kcmil	3.92	1.37	1.52	0.39	0.63	0.72	1.85	—
AL3558	5/8	350 Kcmil	5.32	2.00	1.52	0.34	0.75	0.75	2.62	—


COMPRESSION CONNECTORS



Installation Information			
Manufacturer	Tools	Color	Code
T&B	TBM12 TBM14	Green	94
Panduit	CT-920 CT-980	Green	P94
Burndy	Y35 Y45	Green	22
Celestra	A45	Green	94

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL4112	1/2	400 Kcmil	4.72	1.25	1.65	0.37	0.50	0.81	2.66	—
AL4112-62	1/2	400 kcmil	4.95	1.88	1.62	0.43	0.88	0.76	2.26	—
AL4158-52	5/8	400 kcmil	4.57	1.26	1.62	0.43	0.63	0.76	2.50	—
AL4158-62	5/8	400 kcmil	4.95	1.88	1.62	0.43	0.88	0.76	2.26	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	40TON TBM8-750	Pink	99
Panduit	-	Pink	-
Burndy	Y39 Y644M	Pink	400
Celestra	A45	Pink	99

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL5112	1/2	500 Kcmil	4.84	1.25	1.79	0.38	0.50	0.90	2.66	—
AL5112-52	1/2	500 Kcmil	5.44	1.51	1.80	0.48	0.63	0.84	3.00	—
AL5112-62	1/2	500 kcmil	4.64	1.37	1.80	0.48	0.63	0.84	2.34	—
AL5158	5/8	500 kcmil	5.59	2.00	1.79	0.38	0.75	0.90	2.66	—
AL5158-52	5/8	500 kcmil	5.44	1.51	1.80	0.48	0.63	0.84	3.00	—
AL5158-62	5/8	500 kcmil	5.18	1.91	1.80	0.48	0.88	0.84	2.34	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM12 TBM14M	Black	106
Panduit	CT-920 CT-980	Black	P106
Burndy	Y35 Y45	Black	24
Celestra	A45	Black	106

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL6158	5/8	600 Kcmil	5.49	2.00	1.92	0.37	0.75	0.99	2.56	—
AL6158-62	5/8	600 kcmil	5.28	1.88	1.96	0.52	0.88	0.92	2.47	—

COMPRESSION CONNECTORS




Installation Information

Manufacturer	Tools	Color	Code
T&B	TBM5 TBM6	Yellow	62
Panduit	-	Yellow	-
Burndy	MY29 Y644M	Yellow	16
Celestra	A45	Yellow	62

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL7112-62	1/2	700 Kcmil	4.86	1.34	2.06	0.4	0.63	1.06	2.46	—
AL7158	5/8	700 kcmil	5.81	2.00	2.04	0.38	0.75	1.06	2.75	—
AL7158-62	5/8	700 kcmil	5.40	1.88	2.06	0.4	0.88	1.06	2.46	—

COMPRESSION CONNECTORS



Installation Information			
Manufacturer	Tools	Color	Code
T&B	12 TON 15TON	Yellow	115
Panduit	-	Yellow	-
Burndy	-	Yellow	-
Celestra	A45	Yellow	115

Cat. Nos	Wire Size		Dimension (in.)							Std. Pkg.
	Bolt Size	Cable Size AL/CU	A	B	C	D	F	ID	H	
AL7512-52	1/2	750 Kcmil	6.25	1.82	2.18	0.56	0.88	1.03	3.38	—
AL7558	5/8	750 kcmil	5.96	2.00	2.13	0.4	0.75	1.10	2.90	—
AL7558-52	5/8	750 kcmil	6.25	1.82	2.18	0.56	0.88	1.03	3.38	—