


Metric connectors for copper conductor

One - Hole



Cat. Nos	Conduct Size sq.mm				Dimensions mm					Std. Pkg.
	Stranded	Flexible	2r	5f / 6f	Stud	B	C	R	ID	
J08AN0814A	8	-	-	-	—	0.50	0.45	0.18	0.18	100
J08AN0856A	8	-	-	-	—	0.62	0.56	0.18	0.18	100
J08AN0838A	8	-	-	-	—	0.62	0.56	0.18	0.18	100
J06AN0610A	6	-	-	-	—	0.52	0.49	0.20	0.22	100
J06AN0614A	6	-	-	-	—	0.52	0.49	0.20	0.22	100
J06AN0656A	6	-	-	-	—	0.64	0.60	0.20	0.22	100
J06AN0638A	6	-	-	-	—	0.64	0.60	0.20	0.22	100
J04AN0410A	4	-	-	-	—	0.57	0.55	0.25	0.27	100
J04AN0414A	4	-	-	-	—	0.57	0.55	0.25	0.27	100
J04AN0456A	4	-	-	-	—	0.65	0.62	0.25	0.27	100
J04AN0438A	4	-	-	-	—	0.65	0.62	0.25	0.27	100
J02AN0110A	2	-	-	-	—	0.71	0.70	0.25	0.36	100
J02AN0114A	2	-	-	-	—	0.71	0.70	0.25	0.36	100
J02AN0156A	2	-	-	-	—	0.71	0.70	0.25	0.36	100
J02AN0138A	2	-	-	-	—	0.85	0.70	0.25	0.36	100
J02AN0176A	2	-	-	-	—	0.89	0.77	0.25	0.36	100
J02AN0112A	2	-	-	-	—	0.85	0.77	0.25	0.36	100
J01AN1014A	1AN-1/0	-	-	-	—	0.85	0.77	0.28	0.40	100
J01AN1056A	1AN-1/0	-	-	-	—	0.94	0.77	0.28	0.40	100
J01AN1038A	1AN-1/0	-	-	-	—	0.94	0.77	0.28	0.40	100
J01AN1076A	1AN-1/0	-	-	-	—	0.85	0.77	0.28	0.40	100
J01AN1012A	1/0	-	-	-	—	0.85	0.77	0.28	0.40	100
J10AN2014A	1/0AN-2/0	-	-	-	—	0.94	0.84	0.30	0.44	100
J10AN2056A	1/0AN-2/0	-	-	-	—	0.92	0.84	0.30	0.44	100
J10AN2038A	1/0AN-2/0	-	-	-	—	0.92	0.84	0.30	0.44	100
J10AN2076A	1/0AN-2/0	-	-	-	—	0.94	0.89	0.30	0.44	100
J10AN2012A	1/0AN-2/0	-	-	-	—	0.94	0.89	0.30	0.44	100
J10AN2058A	2/0	-	-	-	—	0.94	0.89	0.30	0.44	100
J20AN3014A	2/0AN-3/0	-	-	-	—	0.93	0.95	0.32	0.51	100
J20AN3056A	2/0AN-3/0	-	-	-	—	0.93	0.95	0.32	0.51	100
J20AN3038A	2/0AN-3/0	-	-	-	—	0.98	0.95	0.32	0.51	100
J20AN3076A	2/0AN-3/0	-	-	-	—	0.98	0.95	0.32	0.51	100
J20AN3012A	3/0	-	-	-	—	0.98	0.95	0.32	0.51	100
J30AN4056A	3/0AN-4/0	-	-	-	—	1.02	1.04	0.32	0.56	100
J30AN4038A	3/0AN-4/0	-	-	-	—	1.03	1.04	0.32	0.56	100
J30AN4076A	3/0AN-4/0	-	-	-	—	1.03	1.04	0.32	0.56	100
J30AN4012A	4/0	-	-	-	—	1.03	1.04	0.32	0.56	100
J40AN2514A	4/0AN-250MCM	-	-	-	—	1.13	1.14	0.35	0.63	100
J40AN2556A	4/0AN-250MCM	-	-	-	—	1.13	1.14	0.35	0.63	100
J40AN2538A	4/0AN-250MCM	-	-	-	—	1.13	1.14	0.35	0.63	100
J40AN2576A	4/0AN-250MCM	-	-	-	—	1.24	1.14	0.35	0.63	100
J40AN2512A	250MCM	-	-	-	—	1.24	1.14	0.35	0.63	100